

M86-02**8086 Microprocessor Trainer Kit**

M86-02 is a single board Microprocessor Trainer Kit based on 16 bit 8086 Microprocessor, which is widely used to train engineers to develop software/hardware for any industrial process & control. This Kit consists of power-full Monitor EPROM, RAM, I/O Lines, Timer/Counter, Serial, LCD Display and Keyboard for Man to Machine Interface.

Features

- ❖ 16K Bytes of EPROM with 16K bytes of Battery Backup RAM.
- ❖ 72 I/O Lines, Three Channel Timer/Counter, PC Serial Interface using USART, Interrupt Controller.
- ❖ 20x2 LCD Display with 101 ASCII Keyboard.
- ❖ Power-full Command like Single Stepping, Break Point, Full Clock Execution, Examine Memory/ Register.
- ❖ Uploading & Downloading to and from PC in Windows98/XP/NT.
- ❖ In-Built Power Supply.

Specifications

- 8086/8088 CPU operating at 2.5/5MHz
- 8086 Processor can be replaced by 8088 Processor
- On-board sockets provided to facilitate the

use of 8087 Co-processor and 8089 I/O Processor

- 16K bytes of RAM using two nos. of 6264 with Battery Backup expandable up to 256KB.
- 16K bytes of powerful monitor EPROM using two nos. of 27512
- 72 I/O lines through 3 nos. of 8255 brought at 26 Pins FRC Connector to interface with IC-XX Series.
- 16 bit Timer/Counter through 8253 brought out at 20 Pins FRC Connector.
- RS-232C interface using 8251 brought out at 9 Pins D-Type Connector.
- On-board Interrupt controller using 8259 brought out at 20 Pins FRC Connector.
- On-board using ADC 0809 & DAC 0800 .
- On-board Real Time Clock using RTC-6424.
- On-board Temperature sensor using Lm35.
- 8 bit digital switch for 8 digital input and 8 led for 8 digital output.
- 20x2/40x2/20x4 Alphanumeric LCD Display with Backlite
- 101 ASCII Keyboard interface using 89c2051 operating @ 12MHz
- Powerful Commands like Examine/Edit Memory, Examine/Edit Register, Single stepping, Execution, Block Move can be used through ASCII Keyboard.
- On-board Single Line Assembler & Disassembler.
- Facility for Downloading/Uploading files from/to PC.
- All address, data & control lines are available on KXT Bus 50 pin FRC Connector to interface with SC-XX Series.
- All ICS are mounted on IC Sockets.
- Bare board Tested Glass Epoxy SMOBC PCB is used.
- In-Built Power Supply of +5V/2A, ±12V/250mA
- Attractive ABS Plastic enclosures.
- User's Manual with sample programs.

Note : Specifications can be altered without notice in our constant efforts for improvement.